

cool  
by Carrier

**SUPRA<sup>®</sup>**

***Solutions for all your  
distribution needs.  
Supra<sup>®</sup> range performance  
for refrigerated trucks.***



**Carrier**  
**TRANSICOLD**



# SUPRA®

## SUPERIOR PERFORMANCE

The Supra® range achieves superior pulldown and accurate temperature control at all set points. This performance is supported by a large range of evaporators with electric fans providing constant airflow independent of engine speed. Available in multi-temperature throughout the range, Supra® offers enhanced load protection for all truck applications.

## HIGH CAPACITY

Extended with three high capacity models, the Supra® range is available up to 12 000 Watts. New fans increase airflow by 15% for quick temperature recovery and improved air management. The use of a 7 mm condenser and smaller compressor improve the unit's efficiency thanks to lower fuel consumption per Watt delivered.

## ROBUST DESIGN

Building on hundreds of thousands of operating hours, the Supra® range demonstrates a robust design both for aesthetics (strong composite material) and components (easy start) to extend unit lifetime and reduce downtime. Maintenance time is also optimised thanks to easy accessibility.

## INTEGRATING IN YOUR WORKING ENVIRONMENT

Tell us your needs, choose your unit: 7 standard units for volumes from 30 to 90m<sup>3</sup>, multi-temperature available throughout the range, nose-mount, undermount, silent and extreme climates versions\*.

The Supra® range offers extreme flexibility to ensure you have the right unit for your operation. The silent version (X Model) drastically reduces noise levels to blend into your distribution area.

\* For extreme climates versions, please consult the Supra Nordic and Oasis brochures.

Developed for distribution environments with multiple doors openings. You can rely on the high performance of the Supra® range to meet the needs of your challenging operation.



|                   |                | REFRIGERATION CAPACITY (Watts)** |       |         |       | AIRFLOW (m3/h) | WEIGHT incl. Evaporator (kg) |      |      |
|-------------------|----------------|----------------------------------|-------|---------|-------|----------------|------------------------------|------|------|
|                   |                | Road                             |       | Standby |       |                | S                            | T    | X    |
|                   |                | 0°C                              | -20°C | 0°C     | -20°C |                |                              |      |      |
| Mono temperature  | Supra 450      | 4365                             | 2515  | 3810    | 2240  | 1590           | 340                          | 343  | N/A  |
|                   | Supra 550      | 5455                             | 3165  | 4670    | 2770  | 2210           | 391                          | 394  | N/A  |
|                   | Supra 750      | 6780                             | 3750  | 5920    | 3120  | 2320           | 429                          | 432  | 437  |
|                   | Supra 850      | 7800                             | 4900  | 6450    | 4240  | 2500           | 461                          | 464  | 466  |
|                   | Supra 1050     | 9100                             | 5600  | 7800    | 5000  | 3350           | 617                          | N/A  | 621  |
|                   | Supra 1150     | 10500                            | 6350  | 8900    | 5400  | 3350           | 626                          | N/A  | 630  |
|                   | Supra 1250     | 12050                            | 6990  | 9100    | 6300  | 3350           | 636                          | N/A  | 640  |
| Under-mount       | Supra 900U     | 9100                             | 4870  | 8050    | 4270  | 3454           | N/A                          | 453  | N/A  |
|                   | Supra 1100U    | 10710                            | 6140  | 9640    | 5600  | 3608           | N/A                          | 558  | N/A  |
| Multi temperature | Supra 750 MT   | 6140                             | 3810  | 5560    | 3840  | Up to 2500     | 411*                         | 414* | 419* |
|                   | Supra 850 MT   | 6300                             | 4490  | 5000    | 3750  | Up to 2500     | 443*                         | 446* | 448* |
|                   | Supra 1150 MT  | 11150                            | 6450  | 9150    | 5600  | Up to 3600     | 576*                         | N/A  | N/A  |
|                   | Supra 1250 MT  | 11600                            | 7200  | 9800    | 6350  | Up to 3600     | 586*                         | N/A  | N/A  |
|                   | Supra 1150U MT | 10700                            | 5960  | 10200   | 5750  | Up to 3600     | N/A                          | 566* | N/A  |

\* Condenser section only

\*\* Ambient temperature at +30°C (per A.T.P. procedure)

## ACCESSORIES

- Battery
- Battery box
- 75 l, 90 l or 200 l fuel tank
- Automatic phase reverser
- Oil filter bypass
- Oil drain extension
- Fuel heater
- Control panel extension cable
- Supply air sensor
- Door switch
- Waterproof box for cab command
- DataCOLD 300 & 600



Stage V\* standards for diesel engines (\*European regulations for Non Road Mobile Machinery (NRMM) specified by Directive EU/2016/1628).

All units running on R542A refrigerant.



600 Carrier service stations in Europe, Russia, Middle East and Africa

Carrier Transicold Europe S.C.S.  
Le Cristalia  
3 rue Joseph Monier  
F-92500 Rueil-Malmaison  
Phone : +33 (0)1 41 42 28 00  
Fax : + 33 (0)1 41 42 28 28  
[www.carriertransicold.eu](http://www.carriertransicold.eu)